

Appln. No. 09/717,767

Attorney Docket No. 5709-159

II. Listing of Claims

1. (Currently Amended): A two piece weatherstrip for a motor vehicle comprising, in combination,

a cover including a first flange portion, a second flange portion and a centrally disposed web, said first and second flange portions defining an outer surface,

a body including a first slot and an adjacent first face and ~~a second an~~ adjacent, oppositely disposed second slot and an adjacent second face, one of said slots adapted to receive said web and ~~another of said slots~~ second slot adapted to receive a flange of said motor vehicle, at least one wiper flange extending from said first face, a flexible flange adapted to engage a portion of said motor vehicle and a recess adjacent between said flexible flange and said second face for receiving a portion of one of said flange portions of said cover.

2. (Currently Amended): The two piece weatherstrip of Claim 1 wherein said one of said flange portions defines a radiused end and said recess of said body ~~defines a~~ is complementarily radiused recess.

3. (Original): The two piece weatherstrip of Claim 1 further including flocking disposed on said at least one wiper flange.

4. (Original): The two piece weatherstrip of Claim 1 including at least two wiper flanges.

5. (Cancelled):

6. (Original): The two piece weatherstrip of Claim 1 wherein said body further includes an S-shaped metal insert.

7. (Original): The two piece weatherstrip of Claim 1 wherein said body includes pluralities of obliquely disposed webs in said slots.

8. (Original): The two piece weatherstrip of Claim 1 wherein said centrally disposed web of said cover includes an asymmetrical notch.

BRINKS
HOFFER
GILSON
BLONE

Appl. No. 09/717,767

Attorney Docket No. 5709-159

9. (Currently Amended): A two piece weatherstrip for a vehicle comprising, in combination,

a cover including first and second flanges defining an outer surface and a centrally disposed web extending from said cover on a side opposite said outer surface, and

a body including a pair of adjacent, oppositely disposed slots, one of said slots adapted to receive said web of said cover and another of said slots adapted to receive an edge of said vehicle, a third flange extending from said body adjacent said one of said slots and adapted to engage a portion of said vehicle, a recess adjacent said third flange adapted to receive a portion of one of said flanges of said body cover and a wiper extending from said body adjacent said another of said slots and adapted to engage a window, ~~one of said slots adapted to receive said web of said cover and another of said slots adapted to receive a flange of said vehicle.~~

10. (Original): The two piece weatherstrip of Claim 9 further including low-friction material on said wiper.

11. (Original): The two piece weatherstrip of Claim 9 wherein said body further includes an S-shaped metal insert.

12. (Currently Amended): The two piece weatherstrip of Claim 9 wherein one of said flanges defines a radiused end and said recess of said body ~~defines a~~ is complementarily radiused ~~recess adapted to receive said radiused end.~~

13. (Original): The two piece weatherstrip of Claim 9 wherein said body includes pluralities of obliquely disposed webs in said slots.

14. (Original): The two piece weatherstrip of Claim 9 wherein said centrally disposed web of said cover includes an asymmetrical notch.

15. (Currently Amended): A two piece outer belt weatherstrip for a motor vehicle door comprising, in combination,

BRINKS
HOFFER
GILSON
ALONE

Appln. No. 09/717,767

Attorney Docket No. 5709-159

a cover including first and second flanges defining an outer surface and a centrally disposed web, and

a body including an S-shaped metal channel and defining a first slot and a second adjacent, oppositely disposed slot, one of said slots adapted to receive said centrally disposed web of said cover and another of said slots adapted to receive a flange of said vehicle, a wiper flange extending from said body adjacent said another of said slots, a vehicle engaging edge and a recess adjacent between said vehicle engaging edge and said one of said slots for receiving an end portion of one of said first and second flanges, ~~one of said slots adapted to receive said centrally disposed web of said body and another of said slots adapted to receive a flange of said vehicle.~~

16. (Original): The two piece outer belt weatherstrip of Claim 15 further including flocking disposed on said at least one wiper flange.

17. (Original): The two piece outer belt weatherstrip of Claim 15 wherein said body includes pluralities of obliquely disposed webs in said slots.

18. (Previously Presented): The two piece outer belt weatherstrip of Claim 15 wherein said centrally disposed web of said cover includes an asymmetrical notch.

19. (Original): The two piece outer belt weatherstrip of Claim 15 including at least two wiper flanges.